

1146EPZN





Description

1 tower with roof, 1 tower with gable roof, 1 triangular platform, 4 square platforms, 1 tubular bridge, 1 tunnel bridge, 1 long slide, 1 deep slide, 2 walls with decorative cuts, 10 safety HDPE boards with decorative cuts, 2 square landings, 4 entrance, 6 climbing bars, 2 metal bars over the slide, 19 metal fittings to be installed in the ground

> Model type Serial number Equipment name

Modulair 1146EPZN Tower 19 1146

Join the action!



Tower 19 1146

	Product line	Action Orbis Wood Modulair
	Age range	3 - 12
	Unit measurements	510cm x 1055cm x 390cm
	Required surface area	835cm x 1605cm
	Impact area	107m²
970	Free height of fall	200cm
1369	Material	Bearing posts have a diameter of 12 cm and are made of glue-laminated, round, wood, fixed 10 cm above the ground level with metal anchors. Antislip platforms. Roofs, security elements and panels are made of HDPE (high durable polyethylene) boards with pattern cuttings. Sliding surface is made of acid-proof, stainless steel sheet. Ropes made of polypropylene with a steel core, thickness 16-18 mm, vandalism and UV resistant. All fittings and connectors are weather and UV resistant. Wood elements are oiled or covered with a colour glaze. Steel elements are protected against corrosion by zinc primer and powder paint coating.
	Heaviest part	120kg
	Largest part	80cm - 450cm
	Spare parts	Available
	Installation time without grondwork	24 hour(s) / 3 person(s)
	Special tools	Included
	Anchoring	Poles are fixed in the ground at a depth of 60 cm on steel anchors. Concrete according to the assembly instructions.
	Remarks	This equipment is also available with hot dip galvanized posts. Prices on request.