

1109EPZN





Description

1 tall castle tower, 1 tower with triangular roof, 1 square platform, 1 deep slide, 1 slide 104, 1 ladder bridge, 1 spiral ladder, 6 safety HDPE boards with decorative cuts, 1 wall with decorative cut, 5 triangular landings, 1 square platform, 2 entrance, 2 climbing bars, 1 metal bar over the slide.

> Model type Serial number Equipment name

Modulair 1109EPZN Castle Tower 9 1109

Join the action!



Castle Tower 9 1109

| 2 | Product line | Action Orbis Wood Modulair |
|---|--|---|
| B B B B B B B B B B B B B B B B B B B | Age range | 3 - 12 |
| | Unit measurements | 560cm x 720cm x 403cm |
| | Required surface area | 1070cm x 1050cm |
| | Impact area | 62m² |
| 688 | Free height of fall | 200cm |
| | Material | Bearing posts have a diameter of 12 cm and are made of glue-laminated, round, wood, fixed 10 cm above the ground level with metal anchors. Antislip platforms. Roofs, security elements and panels are made of HDPE (high durable polyethylene) boards with pattern cuttings. Sliding surface is made of acid-proof, stainless steel sheet. Ropes made of polypropylene with a steel core, thickness 16-18 mm, vandalism and UV resistant. All fittings and connectors are weather and UV resistant. Wood elements are oiled or covered with a colour glaze. Steel elements are protected against corrosion by zinc primer and powder paint coating. |
| | Heaviest part | 90kg |
| | Largest part | 350cm - 80cm |
| | Spare parts | Available |
| | Installation time without grondwork | 10 hour(s) / 3 person(s) |
| | Special tools | Included |
| | Anchoring | Poles are fixed in the ground at a depth of 60 cm on steel anchors. Concrete according to the assembly instructions. |
| | Remarks | This equipment is also available with hot dip galvanized posts. Prices on request. |