





TECHNICAL DATA:

Not easily accessible device,
according to standard EN 1176-1:2017


Top view with falling area



Device dimensions:	Ø 3,50 m
Device height:	2,50 m
Minimum space:	Ø 8,00 m
Falling area:	50,26 m ²
Critical fall height:	1,85 m
Foundations depth:	-1,00m

The device according to EN 1176-1:2017
Playground equipment and surfacing – Part 1:
General safety requirements and test methods

Safety surfaces:
- turf/topsoil, sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 200+100mm
- synthetic surface according to critical fall height



MATERIALS:

Supporting structure:	galvanized steel, powder coated in blue
Arms:	galvanized steel, powder coated in red
Hendles:	steel construction coated with rubber
Chain:	calibrated, made of stainless steel
Caps:	plastic
Foundations:	concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k.
ul. Nowa 32
41-500 Chorzów, Poland

Certificate beholder:
Producer:
Distributor:

GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A.
Saternus Production Sp. z o.o. sp. k.
Saternus Distribution Sp. z o.o. sp. k.