## **15008 COWN SPRING RIDER**



## **TECHNICAL DATA:**

Top view with falling area

		11		1
Device dimensions:	0,65m x 0,49m	1		
Device height:	~0,85m	1		,
Minimum space:	3,65 x 3,40m			1
Critical fall height:	0,45m			340
Falling area:	10,48m <sup>2</sup>	i N		
Depth of foundations:	-0,60m	`		1
		· · · ·	65 365	
		-		

The device according to EN 1176-1:2012 Playground equipment and surfacing – Part 1: General safety requirements and test methods.

## Safety surfaces:

- turf/topsoil, sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 200+100mm
- synthetic surface according to critical fall height

-65 -365 +0,85 +0,45 ±0,00

## **MATERIALS:**

Decorative elements:	HDPE sheet	
Handles, leg supports:	stainless steel pipes	
Steel elements:	galvanized steel, powder coated	
Spring:	spring steel, galvanized and powder coated in red	
Caps:	plastic	
Foundation base:	steel structure	
Foundations:	concrete class min. C12/15	



Certificate beholder: Producer: Distributor:

 SATERNUS DISTRIBUTION Sp. z o.o. sp.k.
 GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A. Saternus Production Sp. z o.o. sp. k. Saternus Distribution Sp. z o.o. sp. k.