



## **TECHNICAL DATA:**

Not easy accessible device, according to standard EN 1176-1:2017

Device dimensions: 4,91 x 4,22m

Device height: 2,52m

Minimum space: 8,35 x 7,72m

Falling area: 44,86m²

Critical fall height: 2,20m


Foundations depth: -0,60m


The device according to EN 1176-1:2017 Playground equipment and surfacing – Part 1: General safety requirements and test methods

## Safety surfaces:

- sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 300+100mm
- synthetic surface according to critical fall height

## Top view with falling area





**COMPONENTS: MATERIALS:** Tower without roof, platform 1,36m: 1 pc glued laminated pine timber, Construction poles: Climbing wall 1,36m: 1 pc rounded at the edges, varnish Vertical ladder: 2 pcs painted dark brown Slide 1,36m: 1 pc Anchors: galvanized steel Fireman's pole 1,36m: 1 pc Flat decorative elements: HDPE sheets Arched rope net: 1 pc Platforms: impregnated pinewood boards, with machined anti-skid surface, Steel elements: galvanized steel, powder coated Surface of slope slide: stainless steel, Climbing walls: waterproof plywood, climbing grips, based on resins polypropylene braided with a steel, Ropes: interconnected by plastic fasteners Caps: plastic Foundations: concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k. ul. Nowa 32 41-500 Chorzów, Poland

Certificate beholder: Producer: Distributor: GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A. Saternus Production Sp. z o.o. sp. k. Saternus Distribution Sp. z o.o. sp. k.