

TECHNICAL DATA:

Not easy accessible device, according to standard EN 1176-1:2017


Device dimensions: 9,91 x 7,80m
Device height: 3,70m
Minimum space: 13,70 x 11,07m
Falling area: 92,20m²
Critical fall height: 2,20m
Foundations depth: -0,60m


The device according to EN 1176-1:2017 Playground equipment and surfacing – Part 1: General safety requirements and test methods

Safety surfaces:

- sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 300+100mm
- synthetic surface according to critical fall height

Top view with falling area





COMPONENTS:		MATERIALS:	
Tower without roof, platform 0,60m: Tower without roof, platform 0,90m:	1 pc 1 pc	Construction poles:	galvanized steel square profile, powder coated in gray galvanized steel HDPE sheets,
Tower with roof, platform 0,90m: Tower with roof, platform 1,36m: Slope gangway 0,90m:	1 pc 1 pc 1 pc	Anchors: Flat decorative elements:	
Vertical ladder: Slide 0,90m:	1 pc 1 pc	Platforms, gangways:	impregnated pinewood boards, with machined anti-skid surface,
Slide 1,36m: Slope bridge:	1 pc 1 pc	Steel elements:	galvanized steel, powder coated
Movable bridge: Horizontal ladder:	1 pc 1 pc	Chains: Surface of slope slide:	galvanized steel stainless steel,
Vertical rope net:	1 pc 1 pc 1 pc	Horizontal ladder:	sides made of HDPE rungs: stainless steel
		Ropes:	polypropylene braided with a steel, interconnected by plastic fasteners
		Caps: Foundations:	plastic concrete min. C12/15 standard
		i dunuations.	Concrete min. C12/13 Standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k. ul. Nowa 32 41-500 Chorzów, Poland

Certificate beholder: Producer: Distributor: GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A. Saternus Production Sp. z o.o. sp. k. Saternus Distribution Sp. z o.o. sp. k.