

TECHNICAL DATA:

Not easily accessible device, according to standard EN 1176-1:2017

Device dimensions: 2,06 x 5,57m

Device height: 2,25m


Minimum space: 6,10 x 9,60m

Falling area: 45,70 m²

Critical fall height: 2,20m

Foundations depth: -0,60m


Top view with impact area



The device according to EN 1176-1:2017 Playground equipment and surfacing – Part 1: General safety requirements and test methods

Safety surfaces:

- sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 200+100mm
- synthetic surface according to critical fall height



LIST OF ELEMENTS:		MATERIALS:	
Climbing rope:	2 pcs	Construction poles:	steel square profiles, galvanized,
Climbing wall:	1 pc		powder coated in gray
Fireman's pole:	1 pc	Steel elements:	galvanized steel, powder coated
Rectilinear entery ropenet:	1 pc	Ropes:	polypropylene braided with a steel,
Vertical ladder:	2 pcs		interconnected by plastic fasteners
Vertical ropenet:	3 pcs	Climbing wall:	shuttering waterproof plywood,
			climbing grips made of material,
			based on resins
		Caps:	plastic
		Foundations:	concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k. ul. Nowa 32 41-500 Chorzów, Poland

Certificate beholder: Producer: Distributor: GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A. Saternus Production Sp. z o.o. sp. k. Saternus Distribution Sp. z o.o. sp. k.